


Door Tablet CRE

Workspace Signage Touch Display



Purpose-built premium display placed outside your meeting rooms running our Door Tablet application



CRESTRON TSS-1070 10.1”



Easy to Install

Works “out of the box” and comes with all the fixtures and fittings needed to get it up where it will be seen. It’s easy to mount on any surface including glass, brick and metal. Motion sensors and remote LEDs are available as options.



Sturdy

The screen is tempered glass which means it is tough, easy to clean and will not shatter, crack or deteriorate excessively with time or heavy use. It’s built to last and stay looking good.



LED Lighting visible from all angles

LED lights on the device visible from all angles with additional options to attach external lights within the proximity of the tablet.



Readable at Wide Viewing Angles

The IPS display ensures the screen can be read comfortably at a distance and at wide angles so there’s no need to get up close to read what’s being displayed. Automatic dimming ensures lower power consumption.



Attractive

It is sleek and slim with a 10.1” high resolution (1280 x 800 px) full color touchscreen; meaning it not only looks good, but the display is easy to read and provides smooth interaction.



Power over Ethernet (PoE+) Built-in

With no need to rely on Wi-Fi signals, a single PoE+ cable powers the device giving you the benefit of full power management, saving costs and the environment. Shut down and restart screens as needed.



Features

Orientation display	Landscape/Portrait
Colors	Black, White
PoE+	Yes
Wi-Fi	Yes
Proximity Sensor	Yes
Brightness Controls	Yes
Wall Mountable	Yes

Display

Display Type	TFT active matrix color LCD
Size	10.1" (257 mm) diagonal
Resolution (Max.)	1280 x 800 pixels
Brightness	400 nits
Contrast ratio	1000 : 1
Viewing angle (H/V)	±80° horizontal, ±80° vertical

I/O Interface

Ethernet	RJ45 (10M/100M)
USB	2 x USB 2.0 type A
Audio	Built-in Speakers

Hardware

Dimensions without stand	240 x 149 x 51mm 9.56" x 5.87" x 2.01"
Weight	730g / 1.61 lbs
Mounting	Glass / Surface
Housing	Plastic
Environment	Operating Temp. 0-40°C Humidity: 10% to 95% RH(noncondensing) (non-condensing)
Certification	IC, CE, FCC Part 15 Class B digital device

<https://door-tablet.com> | sales@door-tablet.com

UK: +44 800 910 1131 | USA: +1 407 545 5925

App Software is pre-installed on the Crestron TSS-1070.
Server software is available for download after registration
Tablet apps are also available from Apple, Google and Microsoft stores.

Door Tablet is a trademark of Public.Class Limited. All other trademarks belong to their respective owners.

 **DOOR TABLET**